

VALVES

1705 - Brass Ballvalve with S/S Lever F/F



Nickel-plated brass ballvalve with a stainless steel lever for general purpose applications. Water, Oil, Chemicals and air. 290 PSI. Size 1/4" to 4" BSP Female/Female.

1706 - Brass Ballvalve with S/S Lever M/F



Nickel-plated brass ballvalve with a stainless steel lever for general purpose applications. Water, Oil, Chemicals and air. 290 PSI. Size 1/2" to 2" BSP Male/Female.

1705L - Brass Ballvalve Lockable Lever F/F



Nickel-plated brass ballvalve with a lockable lever for general purpose applications. Water, Oil, Chemicals and air. 290 PSI. Size 1/2" to 2" BSP Female/Female.

1720 - Brass Ballvalve T-Handle F/F



An A.G.A. approved T-Handle ballvalve for low to medium gas applications. Can also be used for oils and some chemicals. 580 PSI. Size 1/4" to 1" BSP Female/Female.

1721 - Brass Ballvalve T-Handle M/F



An A.G.A. approved T-Handle ballvalve for low to medium gas applications. Can also be used for oils and some chemicals. 580 PSI. Size 1/4" to 1" BSP Male/Female.

915 - PVC Full Flow Ballvalve F/F



General purpose BSP threaded PVC ballvalve used in water pumping for residential, industrial and agriculture. 200 PSI. Size 1/2" to 4" BSP Female/Female.

3830 - Brass Mini Ballvalve F/F



Chrome plated brass bodied 2 way ball valve ideal for line isolation, gauge cocks and other manual operations. 150 PSI. Size 1/8" to 3/4" BSP Female/Female.

3831 - Brass Mini Ballvalve M/F




Chrome plated brass bodied 2 way ball valve ideal for line isolation, gauge cocks and other manual operations. 150 PSI. Size 1/8" to 3/4" BSP Male/Female.

PLN3703 - Plasson Plastic Ballvalve F/F



Ideally suited for draining or sampling of water systems and monitoring systems. Entirely made of plastic is ideal for chemicals and potable water. 232 PSI. Size 1/2" to 2" BSP.

3210L - Brass L-Port 3-Way Ballvalve




L-Port valves have a ball that joins two adjacent ports. They are used to direct flow between the centre and one of two side ports.

Bottom Entry Brass 3-Way Ballvalve



Bottom Entry Brass 3-Way Ballvalve

3110T - Brass T-Port 3-Way Ballvalve



T-Port valves can also direct flow between the centre and one of two side ports, They also have a third handle position that connects the centre to both side ports at the same time.

920 - Brass Gatevalve F/F



Gate valves are often used when minimum pressure loss and a free bore is needed. Gate valves are designed for fully open or fully closed service. 200 PSI. Size 1/2" to 4" BSP.

930/931 - Brass Spring Check F/F



Spring check valves have a disc held in place by a spring, which means they can operate in either a vertical or horizontal mounting position. 110 -360 PSI. Size 3/8" to 4"

932 - Brass Swing Check F/F



Swing check valves have a hinged disc which swings into position, and can operate in either horizontal or vertical (upward flow) positions. 200 PSI. Size 1/2" to 4" BSP

933 - Brass Footvalve



A foot valve is a check valve which is located at the inlet end of the suction line of a pump, allowing the pump to remain full of liquid even when not in service. Size 1/2" to 4".

937 - Brass Y-Strainer F/F



Y Strainers are designed to protect piping system components from damage caused by dirt or debris in flowing liquids or gases. 260 PSI. Size 1/2" to 4" BSP.

Side Entry Stainless Steel 3-Way Ballvalve



Stainless steel L-Port & T-Port 3-Way valves are designed to converge and divert the media flow in a piping system. 1000 PSI. Size 3/8" to 2" BSP.

1775 - 1-Pce Stainless Steel Ballvalve F/F



316SS 1-piece ballvalve, reduced bore with lockable lever. Temperature range of -20C to 180C. 1000 PSI W.O.G. Size 1/4" to 3" BSP.

1760 - 2-Pce Stainless Steel Ballvalve F/F



316SS presents good corrosion resistance, strength and fabrication characteristics. 2-Piece with lockable lever. 1000 PSI W.O.G. Temperature -20C to 180C. Size 1/4" to 4" BSP.

1750 - 3-Pce Stainless Steel Ballvalve F/F



316SS presents good corrosion resistance, strength and fabrication characteristics. 3-Piece with lockable lever. 1000 PSI W.O.G. Temperature -20C to 180C. Size 1/4" to 4" BSP.

1781 - Stainless Gatevalve F/F



Stainless steel gatevalves are commonly used where high pressure/temperature and resistance to chemical is needed. 200 PSI W.O.G. Size 1/2" to 4" BSP.

1785 - Stainless Swing Check F/F



Stainless steel swing check valve with hinged disc for 1-way flow of liquids. 200 PSI W.O.G. Size 1/4" to 4" BSP.

1790 - Stainless Y-Strainer F/F



Y Strainers are designed to protect piping systems and components from damage caused by dirt or debris in flowing liquids or gases. 800 PSI W.O.G.. Size 1/4" to 4" BSP.

1795 - Stainless Spring Check F/F



Stainless steel spring check valve with stainless disc held by spring for 1-way flow of liquids in any mounted position. 200 PSI W.O.G. Temperature -20C to 170C. Size 1/4" to 2" BSP.

925 - Butterfly Valves



Butterfly valves are used for on-off or modulating services and are popular due to their light weight, small installation footprint, lower costs, quick operation and availability in very large sizes. These valves can be operated by handles, gears or automatic actuators. Cast iron body with stainless disc and shaft or fully stainless. 232 PSI. Size 2" to 6".